SLAB SCISSOR LIFTS



- Self-propelled electric scissor lifts
- Compact and robust
- Roll-out extension decks for extra reach
- 1.16m wide models rated for outdoor use
- Ideal for construction and maintenance applications



SLAB SCISSOR LIFTS S2632E/2646E/3246E

| DIMENSIONS | \$2632E | \$2646E | \$3246E |
|------------------------------------|---------------|---------------|---------------|
| Max. working height | 10.0m | 10.0m | 11.8m |
| Max. platform height (A) | 8.0m | 8.0m | 9.75m |
| Platform size (stowed) | 0.74m x 2.31m | 1.14m x 2.38m | 1.14m x 2.38m |
| Platform size (extended) | 0.74m x 3.22m | 1.14m x 3.30m | 1.14m x 3.30m |
| Deck extension length (B) | 0.91m | 0.91m | 0.91m |
| Overall width (C) | 0.81m | 1.16m | 1.16m |
| Stowed length (D) | 2.37m | 2.54m | 2.54m |
| Stowed height (E) | 2.33m | 2.36m | 2.51m |
| Stowed height (guardrails folded) | 1.93m | 1.67m | 1.82m |
| Wheelbase | 1.92m | 1.9m | 1.9m |
| Ground clearance (stowed) | 63mm | 101mm | 101mm |
| Ground clearance (elevated) | 19mm | 25mm | 25mm |

| PERFORMANCE | | | | |
|--|---|----------|----------|--|
| Platform capacity (SWL) | 227kg | 454kg | 317kg | |
| Max. operating wind speed (1 person on platform) | Om/s | 12.5m/s | 12.5m/s | |
| Max. drive height | 8.0m | 7.90m | 9.75m | |
| Max. drive speed (elevated) | 0.6km/h | 0.8km/h | 0.8km/h | |
| Max. drive speed (stowed) | 3.2km/h | 3.2km/h | 3.2km/h | |
| Raise/lower time | 20/26sec | 35/60sec | 50/60sec | |
| Gradeability | 25% | 25% | 25% | |
| Inside turning radius | 0.25m | 0.25m | 0.25m | |
| Outside turning radius | 2.34m | 2.5m | 2.5m | |
| Tyres | 38.1cm x 12.7cm non-marking solid rubber | | | |
| Controls | one-hand proportional joystick | | | |
| Drive system | dual front wheel hydraulic motors | | | |

POWER

WEIGHT


Gross weight


Power source


2,224kg 2,359kg


24V 4hp DC electric motor 4 x 6V 240 Ah batteries

TURNING RADIUS









STANDARD FEATURES

- Proportional controls
- 0.9m extension deck
- Tilt alarm
- Swing-out service trays
- Approved for outdoor use with one person on platform (S2646E/S3246E)
- Power line to platform (no sockets)
- Horn
- Hour meter
- CE approved

OPTIONS

3,003kg

- Special paint colours
- Flashing amber beacon
- Airline to platform
- Dual lanyard anchorage points



Vigo Centre, Birtley Road, Washington, Tyne & Wear, NE38 9DA, U.K.

t: +44 (0) 845 1550 057

e: sales@snorkellifts.com

www.snorkellifts.com

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance.